Section 6 GENERAL FACILITIES

INDEX

TITLE	AGENCY ⁽¹⁾	NUMBER	<u>COMMENTS</u>
Protective Facilities:			
Chain Link Fence and Gates	APWA	600-2	
		and 15th 15th	
Retaining Structures:			
Masonry Retaining Wall	AI WA		This standard applies only within public rights-of-way (not private property). For weep holes called out on sheet 3, place 1 ft³ of ½" gravel, wrapped in filter fabric at each weep hole. If drainage is directed toward the top of wall, special design and approval for a concrete swale will be required by the City Engineer.
Over and Display Olaveris Mell			
Concrete Block Slough Wall Concrete Curb Slough Wall			

<u>TITLE</u>	AGENCY ⁽¹⁾	NUMBER	<u>COMMENTS</u>
Subsurface Access:			
600mm (24") Manhole Frame	and CoverAPWA	630-2	is not required per note 2. For note 6, inspections prior to shipment will not be required. A compliance certification delivered to the Engineer from the supplier will be acceptable.
762mm (30") Manhole Frame	and CoverAPWA	632-2	Agency identification is not required per note 2. For note 6, inspections prior to shipment will not be required. A compliance certification delivered to the Engineer from the supplier will be acceptable.
914mm (36") Manhole Frame	and CoverAPWA	633-2	
Steel Step Polypropylene Plastic Step	APWA APWA	635-2 636-1	
Miscellaneous:			
Survey Monument Curb House Number Riding and Hiking Trail Design	COA	642-A	
(1) APWA: American Public V Works Construction" 2006 COA: City of Anaheim S		rnia Chapter – "S	tandard Plans for Public