



NOTES:

- 1. REFER TO STANDARD DRAWINGS OF MANHOLES FOR DETAILS PERTAINING TO MANHOLES ONLY.
- 2. THE TOP 1/2 DIAMETER OF THE PIPE IS TO BE BROKEN OUT TO A NEAT LINE. BROKEN EDGES SHALL BE PLASTERED SMOOTH WITH CEMENT MORTAR.
- 3. THE MAXIMUM NUMBER OF LATERALS INTO A TERMINUS MANHOLE SHALL BE FOUR.
- 4. THE MAXIMUM NUMBER OF LATERALS INTO A KNUCKLE MANHOLE SHALL BE THREE.
- 5. ALL MANHOLES WITH 3 OR MORE CONNECTING LATERALS SHALL BE 5' DIAMETER.

YUCAIPA VALLEY WATER DISTRICT

TERMINUS (CUL DE SAC) MANHOLE

recense,					,	
NC). B	REVISIONS DATE	APPROVED	DRAWN	APPROVED BY ENGINEERING DEPARTMENT	
				CHECKED	Cly June, 98 DATE DATE	C 74
	_			DATE DEC., 96	ADDETED BY BOARD OF BIRECTORS YVWD	2-31
				NO SCALE	PRESIDENT DATE	SHEET 1 OF 1

D:/STND DWG/YVWD/YVWD 9FW/9-31