

6904M2DI 6900Z4 ASSEMBLY



CAUTION:
DO NOT DISASSEMBLE BOLTED GRATES.
CHECK FRAME WIDTH INSIDE BEFORE
SETTING SECTIONS IN CONCRETE.

NOTE: PALLETIZE WITH WOOD BLOCKING SO GRATES ARE SUPPORTED AND STAY FLUSH AND PARALLEL WITH TOP SURFACES OF SIDE FRAMES. ENDS OF SIDE FRAMES MUST BE PARALLEL AND IN-LINE. GRATE MUST NOT EXTEND PAST ENDS OF SIDE FRAMES. GRATE MUST BE FLUSH OR BACK SLIGHTLY. CHECK BOTH ENDS OF ASSEMBLY WITH STRAIGHT EDGE. DOUBLE BAND PALLET, BOTH DIRECTIONS WITH HEAVY STEEL BANDING. DO NOT SHRINK WRAP.



Corporate Headquarters 301 Spring Street PO Box 439 East Jordan, MI 49727-0439 800.874.4100





800.626.4653 EJIW EAST JORDAN www.ejiw.com
WE COVER YOUR INFRASTRUCTURE WADE IN-THE USA

 Weights (lbs./kg.) dimensions (inches/mm., and drawings provided for your guidance.

•We reserve the right to modify specifications without prior notice.

Uncontrolled distribution.

CONFIDENTIAL: This drawing is the property of East Jordan Iron works, Inc., and embodies confidential information, registered marks, trade secret information, and/or know how that is the property of East Jordan Iron Works, Inc. ©Copyright 2009 East Jordan Iron Works, Inc.

PRODUCT NUMBER

00690457B01

DESIGN FEATURES

MATERIALS

GRATE - DUCTILE IRON ASTM A536

FRAME - GRAY IRON ASTM A48 CL35B

DESIGN LOAD

EXTRA HEAVY DUTY

(PROOF LOAD TESTED TO 200,000 LBS.)

COATING

UNDIPPED

OPEN AREA

98 SQ. INCHES

√ DESIGNATES MACHINE SURFACE

REFERENCE INFORMATION

00690011 00690457

DRAWING DETAILS

ORIGINAL DRAWING: JIJ 02/24/10

REVISED BY: SM

SMM 07/06/11