## **NOTES:**

- 1. ALL PARTS SHALL BE STEEL, EXCEPT THAT END SPACERS MAY BE CAST IRON.
- 2. ALL PARTS SHALL BE GALVANIZED AFTER FABRICATION, EXCEPT THAT GRATINGS SHALL BE ASSEMBLED AFTER COMPONENT PARTS ARE GALVANIZED.
- 3. ALL DIMENSIONS ARE FINISHED DIMENSIONS AND INCLUDE GALVANIZING.
- 4. ALL BOLT HOLES SHALL BE 5/8" (16 mm) DIAMETER.
- 5. ALL THREADS SHALL BE NATIONAL COARSE SERIES (NC).
- 6. CENTER SUPPORT ASSEMBLY REQUIRED WHEN TWO OR MORE GRATINGS ARE SPECIFIED ON PLANS.
  - $L=64" (1626 \ \text{mm})$  FOR CURB OPENING CATCH BASIN WITH GRATING(S) AND DEBRIS SKIMMER (SPPWC 301).
  - L = 44" (1118 mm) FOR CURB OPENING CATCH BASIN WITH GRATING(S) (SPPWC 320.)
  - L = 36" (914 mm) FOR CURBSIDE GRATING CATCH BASIN (SPPWC 303).
  - L = 36" (914 mm) FOR GRATING CATCH BASIN-ALLEY (LONGITUDINAL) (SPPWC 304).

STANDARD PLANS FOR PUBLIC WORKS CONSTRUCTION

STANDARD PLAN

311-3